

TECHNICAL DATA SHEET

Ultra Marker

Mohawk Ultra Marker is a perfect tool to have at hand for finishing touch-up details. Use the Ultra Marker to cover up small scratches or to cover-up finished repairs so they become completely invisible.

The Ultra Marker is a full cover marker that seal, stain, and finish in one step.



PRODUCT SPECIFICATIONS

- * Marker, full cover.

PHYSICAL FORM

- * Colour Many colours; M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522.
- * Length 16 cm
- * Operation temperature Recommended temperature between 15°C and 40°C.

USE

- * For indoor use
- * Ready to use.
- * Perfect for quick coverage of smaller scratches, colour shades etc. in wood.
- * The valve tip provides complete control for the user.
- * Light-resistant pigments that seal, colour, and treat.

NOTICE

- * Remember to put on cap when not in use.
- * Contains UV inhibitor.

PACKAGING

- * 12 mixed colours in blister package or single colour packages.

STORAGE

- * Store cold but frost-free.
- * Store up to 1 year.
- * Recommended room temperature between 5° and 40°C.

IMPORTANT!

The following Safety Data Sheet combines all twelve Ultra Marker colours present in the Ultra Marker Mix Pack and thus display values/ingredients for all twelve colours. The specific values/ingredients of each colour are listed in schemes according to the colour name. Contact susanne@woodrepair.dk for further questions.

SAFETY DATA SHEET

Ultra Marker



1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY

1.1 Product identifier

Product name: Ultra Marker

1.2 Relevant information of the substance/mixture and uses advised against

Use: For touch-up of smaller scratches and colour shades etc. in wooden surfaces.

1.3 Details of the supplier of the Safety Data Sheet

Supplier: Wood Repair by Boegh Consult A/S
Charles Lindberghs Vej 6
DK-9430 Vadum, Denmark
Tel: +45 9827 1919
Mail: info@woodrepair.dk
Contact person: Susanne Bøgh

1.4 Emergency telephone number






24H Emergency phone: +45 82121212 Bispebjerg Hospital poisonous line

2. HAZARDS IDENTIFICATION

2.1 Classifications of the product/mixture according to 1272/2008

GHS classification: See scheme Section 3

Symbol(s) of product:

							
GHS02	GHS05	GHS06	GHS07	GHS08			

Signal word: Danger

2.2 Classification according to CLP 1272/2008

GHS hazards statements: Note! Differs from colour to colour. See scheme Section 3 for specific info on colours.

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Irritation, category 2	H315	Causes skin irritation.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

2.3 Other information/dangers:**GHS label precautionary statements**

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

GHS SDS precautionary statements

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. COMPOSITION – INFORMATION ON INGREDIENTS**3.1/2 Ingredients/mixture**

Chemical Name	Cas-No.	Wt. % min-max	GHS symbols	GHS Statements	In these Ultra Marker colours:
ethanol	64-17-5	25 - 75	GHS02	H225	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
titanium dioxide	13463-67-7	2.5 - 40	No Information	No Information	M280-0202, M280-0236,

butanol	71-36-3	10 - 25	GHS02, GHS05, GHS07	H226, H302, H315, H318, H332, H335, H336	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0227, M280-0236, M280-0411, M280-0415, M280-1522,
pm acetate	108-65-6	1.0 - 25	GHS02, GHS07	H226, H332	M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0236, M280-0411, M280-0415, M280-1522,
toluene	108-88-3	10 - 40	GHS02, GHS07, GHS08	H225, H304, H315, H332, H336, H373	M280-0224, M280-0408,
aliphatic petroleum distillates	64742-88-7	0.1 - 2.5	GHS06, GHS08	H304, H331, H372	M280-0202, M280-0218, M280-0236, M280-0411,
aliphatic petroleum distillates	64742-47-8	0.1 - 2.5	GHS06, GHS08	H304, H331	M280-0202, M280-0218, M280-0236, M280-0411,
isopropanol	67-63-0	1.0 - 10	GHS02, GHS07	H225, H302, H319, H336	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
carbon black	1333-86-4	0.1 - 10	GHS02	H251	M280-0209, M280-0224, M280-1522,
petroleum distillate	64742-54-7	0.1 - 1.0	GHS08	H350	M280-0224, M280-0408,
dipropylene glycol monomethyl ether	34590-94-8	1.0 - 2.5	No Information	No Information	M280-0143, M280-0209, M280-0221, M280-0227, M280-0415, M280-1522,
ethylbenzene	100-41-4	0.1 - 1.0	GHS02, GHS07, GHS08	H225, H304, H332, H373	M280-0143, M280-0209, M280-0221, M280-0227, M280-0236, M280-0415, M280-1522,
chromium 2+ or 3+ compounds	117527-94-3	1.0 - 2.5	No Information	No Information	
iron oxide	1309-37-1	2.5 - 25	No Information	No Information	M280-0209,
aliphatic hydrocarbons	8052-41-3	0.1 - 2.5	GHS08	H304, H340, H350, H372	M280-0209, M280-1522,
pigment	proprietary	0.1 - 10	No Information	No Information	M280-0209, M280-0218, M280-0221, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
crystalline silica	14808-60-7	0.1 - 1.0	GHS07	H302	M280-0209, M280-0218, M280-0236, M280-0411, M280-1522,
calcium carbonate	1317-65-3	0.1 - 1.0	No Information	No Information	
Light gas oil	64742-80-9	0.1 - 1.0	GHS06, GHS08	H331, H350	M280-0218,
Barium sulfate	7727-43-7	<0.1	No Information	No Information	M280-1522,

Note! To get a more precise amount of ingredients in an Ultra Marker, send us a request to susanne@woodrepair.dk. The exact percentage (concentration) of ingredients, however, is being withheld as a trade secret.

3.3 Other information

The full text of all H-danger sentences is shown in section 16. Exposure limits shown in section 8.

4. FIRST AID MEASURES

4.1 Description of first aid measures

In general:	In case of doubt or if symptoms persist, always see a doctor. Never induce swallowing by an unconscious person. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Inhalation:	Seek fresh air if you feel discomfort. See a doctor if you continue to feel discomfort.
Skin contact:	Take off all contaminated clothing. Wash skin with plenty of soap and water. See a doctor if you continue to feel discomfort. Wash contaminated clothing before reuse.
Eye contact:	Rinse with plenty of cold water immediately. Remove contact lenses, if present and easy to do so. See an ophthalmologist and continue rinsing during transport.
Ingestion:	Rinse mouth. Do not provoke vomiting, see a doctor.

4.2 Most important symptoms and effects, both acute and delayed

None known

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptoms. Contact the poison line immediately if large quantities have been ingested or inhaled.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguish media: This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

5.2 Special hazards arising from the substance/mixture

Specific dangers: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

5.3 Advice for firefighters

Protection: Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear a self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Protection person: See section 8

6.2 Environmental precautions

Environment: Prevent any material from entering drains or waterways.

6.3 Methods and material for containment and cleaning up

Cleaning methods: Gather spillage into waste drums or plastic bags. Store in container until removal. Clean the area carefully with water.
Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames.
Check specific rules and regulations with the local authorities.

6.4 Reference to other sections

See section 8 and 13

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling: Do not store in same room as groceries. Avoid ignition sources (smoking, flames, pilot lights, and electrical sparks). Ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapour and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapour. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store up to 1 year. To maintain product quality and characteristics store in closed packaging in frost free room. Store in cool well-ventilated space away from incompatible materials.

Packaging: Always store product in identical material to the original packaging. Keep containers closed when not in use.

7.3 Specific and use(s)

To be used only as specified in Technical Data Sheet plus section 1 of this SDS.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION




8.1 Control parameters

Exposure limits:

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING	In these Ultra Marker colours:
Ethanol	Not determined	1000 ppm	1000 ppm	Not determined	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
Pm acetate	Not determined	Not determined	Not determined	Not determined	M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0236, M280-0411, M280-0415, M280-1522,
Toluene	20 ppm	Not determined	200 ppm	300 ppm	M280-0224, M280-0408,
Carbon black	3mg/m3	Not determined	3.5mg/m3	Not determined	M280-0209, M280-0224, M280-1522,
Isopropanol	200 ppm	400 ppm	400 ppm	Not determined	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
Petroleum distillate	Not determined	Not determined	Not determined	Not determined	M280-0224, M280-0408,
Titanium dioxide	10 mg/m3	Not determined	15 mg/m3	Not determined	M280-0202, M280-0236,
Butanol	20 ppm	Not determined	100 ppm	Not determined	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0227, M280-0236, M280-0411, M280-0415, M280-1522,
Aliphatic petroleum distillates	Not determined	Not determined	Not determined	Not determined	M280-0202, M280-0218, M280-0236, M280-0411,
Dipropylene glycol monomethyl ether	100 ppm	150 ppm	100 ppm	Not determined	M280-0143, M280-0209, M280-0221, M280-0227, M280-0415, M280-1522,
Ethylbenzene	20 ppm	Not determined	100 ppm	Not determined	M280-0143, M280-0209, M280-0221, M280-0227, M280-0236, M280-0415, M280-1522,
Chromium 2+ or 3+ compounds	Not determined	Not determined	Not determined	Not determined	
Iron oxide	5mg/m3	Not determined	10mg/m3	Not determined	M280-0209,
Aliphatic hydrocarbons	100 ppm	Not determined	500 ppm	Not determined	M280-0209, M280-1522,
Pigment	Not determined	Not determined	Not determined	Not determined	M280-0209, M280-0218, M280-0221, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
Crystalline silica	0.025mg/m3	Not determined	50µ/m3	Not determined	M280-0209, M280-0218, M280-0236, M280-0411, M280-1522,
Light gas oil	Not determined	Not determined	Not determined	Not determined	M280-0218,
Calcium carbonate	Not determined	Not determined	15 mg/m3	Not determined	
Barium sulfate	5mg/m3	Not determined	15 mg/m3	Not determined	M280-1522,

8.2 Exposure controls

Tech. measures: Ensure effective ventilation. Process ventilation recommended.

General:	Smoking, eating or drinking, as well as storage of tobacco, food and drinks not allowed in working area. Wash hands and other exposed areas with mild soap and water before ingestions of food and beverage or smoking, as well as at the end of work. Ensure access to eye rinsing bottle.
Personal means:	Personal means to be chosen in accordance with current CEN standards and in cooperation with the supplier of personal means.
	  
Inhalation:	Only when sanding - wear sufficient dust mask (type P2) whenever dust limits are exceeded to avoid disturbances. (EN149)
Hand:	Wear rubber gloves in case of long or repeated use. (EN374) Type B – 30 minutes (level 2) against minimum 3 test chemicals. Wash hands thoroughly after handling and before eating or drinking.
Eye:	Use protection goggles if risk of contact with melted product. EN 166
Skin:	Wash skin thoroughly with water and mild soap at breaks and at the end of the working day.
Hygiene:	Wash working clothes regularly.
Environment	Prevent any material from entering drains or waterways.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state Liquid	Colour Many colours	Smell Modererate strong alcohol	pH Not determined		
Flash point 3.89°C – 12.78°C	Boiling point > 37.7 °C	Vapour pressure, mmHg Not determined	Density g/cm3 0.849 - 1.177	Melting point -	
Ignition -	Auto ignition Not determined	Softening point -	Solubility in water Not determined		

9.2 Other information

Above-mentioned properties (9.1) include all Ultra Marker colours. Thus, the range between lowest and highest values in “Flash point” and “Density g/cm3”. Please contact Susanne Bøgh on susanne@woodrepair.dk for precise Flash point and Density g/cm3 values in a specific Ultra Marker colour.

10. STABILITY AND REACTIVITY

10.1 Reactivity	There is no reactivity if used as described in Technical Data Sheet plus section 1.2 of SDS.
10.2 Chemical stability	The product is stable if handled as described in Section 7.
10.3 Possibility of hazardous reactions	None known
10.4 Conditions to avoid	Extreme temperatures will influence the product.

10.5 Incompatible materials Acids, Bases, Oxidizing agents

10.6 Hazardous decomposition prod. Not determined

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity: The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	In these Ultra Marker colours:
1333-86-4	carbon black	>5000 mg/kg Rat	>3000 mg/kg Rabbit	>20 mg/l	M280-0209, M280-0224, M280-1522,
13463-67-7	titanium dioxide	>10000 mg/kg Rat	>10000 mg/kg Rabbit	>20 mg/l	M280-0202, M280-0236,
14808-60-7	crystalline silica	500 mg/kg Rat	No information	>20 mg/l Rat	M280-0209, M280-0218, M280-0236, M280-0411, M280-1522,
1309-37-1	iron oxide	>10000 mg/kg Rat	>5000 mg/kg Rat	>20 mg/l	M280-0209,
64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
108-88-3	toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat	M280-0224, M280-0408,
67-63-0	isopropanol	1870 mg/kg Rat	4059 mg/kg Rabbit	72.6 mg/L Rat	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0227, M280-0236, M280-0408, M280-0411, M280-0415, M280-1522,
71-36-3	butanol	700 mg/kg Rat	3402 mg/kg Rabbit	8000 mg/l Rat	M280-0143, M280-0202, M280-0209, M280-0218, M280-0221, M280-0227, M280-0236, M280-0411, M280-0415, M280-1522,
108-65-6	pm acetate	8532 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L	M280-0202, M280-0209, M280-0218, M280-0221, M280-0224, M280-0236, M280-0411, M280-0415, M280-1522,
64742-47-8	aliphatic petroleum distillates	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>5.2 mg/L Rat	M280-0202, M280-0218, M280-0236, M280-0411,
64742-88-7	aliphatic petroleum distillates	>5000 mg/kg Rat	=>3000 mg/kg Rabbit	>5.28 mg/L Rat	M280-0202, M280-0218, M280-0236, M280-0411,
34590-94-8	dipropylene glycol monomethyl ether	5230 mg/kg Rat	9500 mg/kg Rabbit	>20 mg/l	M280-0143, M280-0209, M280-0221, M280-0227, M280-0415, M280-1522,
8052-41-3	aliphatic hydrocarbons	>5000 mg/kg Rat	3160 mg/kg Rat	21 mg/L Rat	M280-0209, M280-1522,
100-41-4	ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.2 mg/L Rat	M280-0143, M280-0209, M280-0221, M280-0227, M280-0236, M280-0415, M280-1522,
64742-80-9	Light gas oil	>5000 mg/kg Rat	>2000 mg/kg Rabbit	4.6 mg/L Rat	M280-0218,
7727-43-7	Barium sulfate	307000 mg/kg Rat	No information	No information	M280-1522,

Skin corrosion/-irritation	Not classified.
Serious eye damage/-irritation	Not classified.
Respiratory or skin sensitisation	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
STOT-single exposure	Not classified.
STOT repeated exposure	Not classified.
Aspiration hazard	Not classified.
Long-term effects:	Not classified.

11.2. Mixture

Respiratory or skin sensitisation: Contains at least one sensitising substance. May cause an allergic reaction.

12. ECOLOGICAL INFORMATION

12.1 Toxicity - substances	No data available.
12.2 Persistence and degradability	No data available, but expected not to degrade quickly.
12.3 Bioaccumulative potential	No data available.
12.4 Mobility in soil	No data available.
12.5 Results of PBT and vPvB assessment	No data available.
12.6 Other adverse effects	Prevent material from entering the environment

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

Do not flush directly in drain. Sweep up or vacuum up spillage and dispose according to national and local rules and regulations.

14. TRANSPORT INFORMATION

Special transport precautions: No Information.

	ADR/RID	IMDG/IMO
14.1 UN-number	1263	1263
14.2 UN proper shipping name	Flammable liquid	Flammable liquid
14.3 Transport hazard class(es)	3	3
14.4 Packing group	II	II
14.5 Environmental hazard		
MP	-	-
EMS	-	-
14.6 Special precautions for user	-	-
14.7 Transport in bulk according to Annex II of Marpol 73/78 and the BIC Code	T4	T4
Other information	Exemption limit 5 litres	Exemption limit 5 litres

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Ministry of the environment Directive o. 1075 dated 24th November 2011 on classification, packing, labelling, sale and storage of chemical substances and products.

Labour Inspectorate (LI) Directive no. 292 dated April 26th 2001 on Work with substances and material (chemical agents) with changes.

Directive no. 559 dated July 4th 2002 on Specific obligations for producers, suppliers and importers of substances and material in accordance with the Working Environment Act.

LI-Directive no. 507 dated 17th May 2011, with changes.


LI-Guidance 1134-2011 on Exposure limits for substances and materials.

LI-Directive no. 908 dated 27th September 2005 on Measures to prevent risk of Cancer working with substances and material, with changes.

LI- Directive no. 239 dated April 6th 2005 on Youth workers, with changes.
 LI-Guidance no. 1309 dated 18th December 2012 on waste disposal.
 Defence Ministry Direction no. 17 dated 4th January 2010 on flammable liquids.
 LI-Directive no. 301 dated May 13th 1993 on clarification of OAR Code numbers.
 Directive no. 48 dated January 13th 2010 on Waste disposal.
 EC Directive 1272/2008 (CLP), EC Directive 453/2010 (Update CLP)
 EC Directive 1907/2006 (REACH)

Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=2, Inflammability=3, Instability/Reactivity=0, Specific Risk=None.



15.2 Chemical safety assessment

No chemical safety assessment has been made for the product.




Volatile Organic Compounds, Gr / L: 623 - 727 (Gr / L includes / applies to all Ultra Marker colours, reflecting the range between lowest and highest values).

16. OTHER INFORMATION

16.1 Full wording of H-R sentences in section 3:

- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H251 Shelf-heating: may catch fire
- H302 Harmful if swallowed
- H304 may be fatal if swallowed and enters airways.
- H315 Causes skin irritation
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

							
GHS02	GHS05	GHS06	GHS07	GHS08			

Abbreviations:

ADR:	European agreement concerning the international carriage of dangerous goods by Road.
IMDG:	International Maritime Dangerous Goods.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organisation.
RID:	Regulations concerning the International carriage of Dangerous goods by rail.
WGK:	Wassergefährdungsklasse (Water Hazard Class)
PBT:	Persistent, bioaccumulable and toxic
vPvB:	Very persistent, very bioaccumulable.
SVHC:	Substance of very high concern.

Recommended use: Repair of smaller scratches etc. in wood/wooden surfaces (more details on technical sheet).

Personnel to be instructed in correct use of the product. Personnel must read this Safety Data Sheet before using the product including the Technical Data Sheet.

To the best of our knowledge the information given herewith is accurate. However, no liability what so ever is assumed for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein we cannot guarantee that these are the only hazards that exist.

Issued by:

Susanne Bøgh

